

TECHNICAL DATA SHEET

SURFACE COATINGS FEEDSCREED

A three part epoxy resin based material that has been developed for use in feed passages or troughs to produce a smooth, easily cleaned feed surface which is resistant to harsh chemicals and mechanical wear and tear.

PRODUCT BENEFITS:

- Smooth surface encourages increased feed intake by up to 10%.
- Increases ration acceptance less mould/spoilage/dirt.
- Hygienic harbours less potentially pathogenic bacteria to reduce transmission of disease.
- Practical can be used on new or old concrete and in feed troughs.
- Durable withstands heavy machinery, harsh chemicals and pressure washing.
- 25kg will cover up to 10-11m².

TO PREPARE SURFACE:

- Prepare and clean the surface to be treated.
- 2. Allow area to dry thoroughly.
- Mark out area to be treated using duct tape.
- 4. Apply Feedscreed Primer and allow to dry before applying Feedscreed. The Primer should feel tacky at the point when ready to receive Feedscreed coating. Once mixed, the pot life is 20 minutes.

TO PREPARE FEED SCREED:

- 5. Pour pack B into Pack A and mix thoroughly with plasterer's drill and paddle for 3 minutes.
- 6. Pour this mixture into the 20 litre plastic bucket provided.
- 7. Add Pack C to the mixture in plastic bucket whilst stirring continuously. Continue to stir for 3 minutes.
- 8. Apply immediately at a thickness of 2-3mm and squeegee over area to be treated.
- 9. Once area is covered, use a spiked roller in a horizontal and vertical direction.
- 10. Always apply successive mixes to a wet edge.
- 11. Once mixed, the pot life is 20 minutes.
- 12. Allow to dry for 24 hours before use and 3 to 4 days before surface is completely cured.

Shelf life:

1 year from date of manufacture.

Store between 0°C to 25°C. Keep out of direct sunlight.

For health and safety information, please refer to the Safety Data Sheet.



SIZES AVAILABLE:

- Feed Screed Primer Code PSCP
- Feed Screed 25kg (Green) Code PSCG
- Feed Screed 25kg (Natural) Code PSCN
- Feed Screed 25kg (White) Code PSCW
- Feed Screed 25kg (Blue) Code PSCB
- Spiked Roller Code PSCR